

SPECIFICATION**EVER COOL MODEL TC200-6 Oil Circulating Temperature Control Unit**

Heating Capacity:	6kW
Maximum Operating Temperature:	200°C
Heater Control:	Solid State Relay
Cooling Capacity:	20kW
Tank Capacity:	20 litres - stainless steel
Pump Type:	Submersible pump
Maximum Flow/Pressure:	60ltr/min @ 3.5 bar
Pump Power:	0.9kW
Electrical Supply:	400v - 3 ph - 50 Hz + E
Control Voltage:	24v AC
Process Connection IN/OUT:	¾" / ¾"
Cooling Connection:	¾" / ½"
Weight:	47 kg
Dimensions: LxWxH	295 x 575 x 585 mm
Noise Level:	Less than 80 dBA at 1 metre

STANDARD FITTED EQUIPMENT

PID twin digital readout diagnostic controller
Submersible pump which eliminates internal seal leakage
Non-ferrous internal parts
Low watts density, long life incoloy heating element
Large surface area for maximum heat dispersion
Motor protection device
Castors mounted for ease of transport
Manual oil filling
Security thermostat for heater element protection
Solid state relay

Optional Extras:

Double water outlet kit
Flow rate control
External sensor
PT100 process sensor
Return of process temperature indication
Manual filling
Serial interface 4-20mA, RS485, 0-10 volts

